



Mastercool[®] Inc.
"World Class Quality"

55750 COMBUSTIBLE GAS LEAK DETECTOR

55750

FEATURES:

- Six Sensitivity Levels
- Reset Function
- Automatic Warm Up
- Bright LED Light
- Audible Leak Alarm & Visual Leak Size Indicator
- Rechargeable Ni-MH Battery
- Low Battery Indicator
- Custom Molded Carrying Case

SPECIFICATIONS:

- Operating Temp: 0 to 52°C (32-125°F)
- Power Supply: 2 C-Size 1.5V Ni-MH Battery
- Battery Life: 8 hrs per cycle (1000 cycles)
- Warm-Up Time: 25 seconds
- Probe/Core Length: 381mm (15")
- Dimension: 178 x 178mm (7 x 7")
- Weight: .49 kg (1.10 lbs)
- Ultimate Sensitivity: 50 – 1000 ppm

DETECTS:

Acetone, Acetylene, Ammonia, Benzene, Butane, Butanol, Chlorine, Ethane, Ethanol, Gasoline, Hexane, Hydrogen, Hydrogen Sulfide, Isobutane, Methane (natural gas), Methanol, Methyl Acetate, Methyl Chloride, Methyl Ether, Naptha, N-Butane, Pentane, Propane, Propanol, Sulfphur Dioxide and Trichloroethane



• Made in USA