



DUAL VOLTAGE VACUUM PUMP



Slide switch 110/220V, recessed for protection



Vapor discharge/oil fill port, easily removable, contains internal check valve to prevent escape of liquid oil

90063-2V-220 (3 CFM)

High volume fan provides cool air to motor and pump



Non-slip cushion handle

Includes T-fitting with 1/4" flare and 1/2" ACME ports



90066-2V-220 (6 CFM)

Cooling fins to keep temperature cooler during extended motor operation

DUAL VOLTAGE VACUUM PUMP

MODEL	No. of Stages	Free Air Displacement	Ultimate Vacuum	Motor	Pump Speed	Electrical	Power Cord	Shipping weight	Dimensions in cm
90063-2V-220 (3 CFM)	2	85 lit/min (60Hz) 71 lit/min (50Hz)	15 Microns	1/4 HP	2880 RPM	110 V/220 V 50/60 HZ	220V Cable (Shuko)	10.7 kg	35 x 14.3 x 26.5
90066-2V-220 (6 CFM)	2	170 lit/min (60Hz) 140 lit/min (50Hz)	15 Microns	1/3 HP	2880 RPM	110 V/220 V 50/60 HZ	220V Cable (Shuko)	11.2 kg	35 x 14.3 x 26.5
90070-2V-220 (10 CFM)	2	238 lit/min (60Hz) 198 lit/min (50Hz)	12 Microns	1/2 HP	2880 RPM	110 V/220 V 50/60 HZ	220V Cable (Shuko)	14.8 kg	38 x 16 x 28.5

Manifold valve isolates pump from the system testing for leaks Includes 3 inlet ports, 1/4", 3/8" SAE and 1/2" ACME

Gas ballast valve helps prevent oil contamination caused by high moisture.

90070-2V-220 (10 CFM)

