



Model	RECO250S			
Refrigerants	Cat. III:R-12,R-134a,R-401C,R-406A,R-500			
	Cat. IV:R-22,R-401A,R-401B,R-402B,R-407C, R-407D,R-408A,R-409A,R-411A,R-411B,R-412A,R-502,R-509			
	Cat. V:R-402A,R-404A,R-407A,R-407B,R-410A, R-507			
Power	110-127V/60Hz 220-240V 50/60Hz 110-220V 50/60Hz			
Motor	1/2HP AC; Capacitor start			
Max.Current	4A@50Hz 8A@60Hz			
Compressor	Oil-less; air cooled; piston style			
Refrigerant Recovery Rate		Cat. III	Cat. IV	Cat. V
	Vapor	0.23kg/min	0.25kg/min	0.26kg/min
	Liquid	1.57kg/min	1.81kg/min	1.85kg/min
	Push/Pull	4.64kg/min	5.57kg/min	6.22kg/min
Recycling Rate	1.57kg/min	1.81kg/min	1.85kg/min	
High Pressure Shut-off	38bar/550psi			
Low Pressure Shut-off	Optional			
80%O.F.P.Shut-off kit	Optional			
Operating Temp.	0 °C-40°C			
Dimensions	485mm (L)x220mm(W)x365mm(H)			
Net Weight	14kg			