

Supervac Vacuum Pumps

Features:-

- Magnetic safety valve to protect the refrigeration cycle from oil contamination during power outage.
- Vacuum meter with integrated drag indicator enables simple & fast control of the vacuum process.
- Specially designed filter reduces oil mist on nozzle.
- Gauge – glass enables easy oil level monitoring.



Two – stage rotary vane pump.

Compact, portable device for vacuum & cleansing of refrigeration systems of all kinds.

Technical Details –

	Supervac 42	Supervac 85	Supervac 170	Supervac 255
Part No.	1500050001	1500050002	1500050003	1500050004
Pump Rating	1.5Cfm / 42 l/min	3.0Cfm / 85 l/min	6.0Cfm / 170 l/min	9.0Cfm / 255 l/min
Vacuum Stages	2	2	2	2
Poles	4	4	2	2
Final Vacuum	25micron / 0.034mbar	25micron / 0.034mbar	25micron / 0.034mbar	25micron / 0.034mbar
Motor Rating	0.25HP / 190W	0.33HP / 250W	0.5HP / 375W	1.0HP / 750W
Voltage	230V	230V	230V	230V
Frequency	60Hz	60Hz	60Hz	60Hz
Connections	¼” SAE	¼” SAE	¼” SAE	¼” SAE
With Adaptor	5/16” SAE 3/8” SAE	5/16” SAE 3/8” SAE	5/16” SAE 3/8” SAE	5/16” SAE 3/8” SAE
Oil Capacity	250ml	330ml	330ml	590ml
Weight	9.0Kg.	10.7Kg.	11.5Kg.	17.0Kg.
Pressure Gauge	50mm	50mm	50mm	50mm