

HERCULES

The HERCULES is a large-sized tank pump that is designed to be installed with large air conditioners, retail refrigerators and boilers.

- Floor Mounting Location
- Designed for High Delivery Head and Flow Rate
- Oil-Resistant Water Tank and Impeller
- Optional Safety Switch Ass'y
- 1/4-Turn Check Valve for Easy Servicing
- Thermally Protected
- 2 Inlet Holes (30mmΦ)
- CE / ETL Certified

- Power Supply: 110~120V 60Hz or 220~240V 50/60Hz
- Ambient Temperature : 0°C to 50°C
- Thermal Protection : Cut-out at 120°C

HERCULES

MD1000

non

Performance / Características

N4 - 1 - 1	Dower Cumply	Performance(l/hr@Height in Meter)					Maximum Lift		Amps	Watts
Model	Power Supply	0	5	10	12	15	Meter	Ft	Amps	Walls
MD1000	220V 60Hz	648	366	204	-	_	10 . 0m	33	0.99A	220
	230V 50Hz	630	324	156	-	-	9.0m	30	0.88A	187
	120V 60Hz	630	390	180	-	-	10 . 0m	33	1.91A	226

Dimensions / Dimensiones

Model	Weight	Tank Capacity	O.D of Outlet
MD1000	3.13kg	3.8ℓ	3/8"



