

## Recovery unit VRR24L-OS



|                                                          |                                                                                                   |
|----------------------------------------------------------|---------------------------------------------------------------------------------------------------|
| Refrigerants: Category III                               | R-12, R-134a, R-401C, R-500                                                                       |
| Refrigerants: Category IV                                | R-22, R-401A, R-401B, R-402B, R-407C, R-407D, R408A, R-409A, R-411A, R-411B, R-412A, R-502, R-509 |
| Refrigerants: Category V                                 | R-402A, R-404A, R-407A, R-410A, R-507                                                             |
| Power supply                                             | 230/50 V/Hz                                                                                       |
| Power                                                    | 1 KM                                                                                              |
| Motor speed                                              | 1450 rpm                                                                                          |
| Maximum current draw                                     | 5 A                                                                                               |
| Compressor                                               | Oil-less, air-cooled, piston style                                                                |
| Automatic safety shut-off                                | 38,5/3850 bar/kPa (558 psi)                                                                       |
| Recovery rate: Category III - Vapor / Liquid / Push/pull | 0,40 / 3,00 / 7,50 kg/min                                                                         |

## Recovery unit VRR24L-OS

|                                                         |                           |
|---------------------------------------------------------|---------------------------|
| Recovery rate: Category IV - Vapor / Liquid / Push/pull | 0,50 / 3,50 / 8,50 kg/min |
| Recovery rate: Category V - Vapor / Liquid / Push/pull  | 0,50 / 3,50 / 9,50 kg/min |
| Operating temperature                                   | 0 ÷ 40 °C                 |
| Dimensions                                              | 450 x 250 x 355 mm        |
| Weight                                                  | 14,7 kg                   |

Pictures of some products may vary. Every effort has been made to ensure that the information contained in this catalog is correct. Due to constant technological development, we reserve the right to make changes without notice.

## Recovery unit VRR24L-OS

Refrigerant recovery unit with oil separator is used for the recovery of refrigerant HFC and HCFC.

The main features:

- rapid recovery of refrigerant
- with oil separator
- high efficiency
- equipped with a high and low pressure gauge
- manual reset
- one knob for easy operation
- function of turned off by reaching 80% filling the bottle of refrigerant

